

HI SOLIDS DRY BRIGHT FLOOR POLISH

MOP ON & LEAVE TO DRY TO A HARD SHINE

DOES NOT REQUIRE BUFFING BUT WILL IMPROVE FINISH

EXCELLENT SLIP RESISTANCE

012.002




DESCRIPTION

MERLIN F07 HI SOLIDS DRY BRIGHT FLOOR POLISH is a high quality acrylic polymer polish formulated with thermoplastic polymers. MERLIN F07 HI SOLIDS DRY BRIGHT FLOOR POLISH does not require machine buffing. MERLIN F07 HI SOLIDS DRY BRIGHT FLOOR POLISH is not harmed by solutions of neutral cleaning materials, but is stripped using MERLIN F01 RINSE FREE FLOOR POLISH REMOVER or MERLIN F02 HEAVY DUTY FLOOR POLISH REMOVER.

USES

MERLIN F07 HI SOLIDS DRY BRIGHT FLOOR POLISH is suitable for use on PVC, thermoplastic floors, linoleum, rubber, sealed cork, sealed wood, asphalt, terrazzo, marble and stone.













DILUTIONS AND DIRECTIONS

PREPARATION: For optimum results thorough preparation of the floor must be undertaken. The floor must be thoroughly cleaned to completely remove dirt, grease and old polish films by using a quality floor polish remover such as MERLIN F01 RINSE FREE FLOOR POLISH REMOVER or MERLIN F02 HEAVY DUTY FLOOR POLISH REMOVER. The floor must be well rinsed with water & allowed to dry before applying MERLIN F07 HI SOLIDS DRY BRIGHT FLOOR POLISH.





APPLICATION: Apply a generous film of **MERLIN F07 HI SOLIDS DRY BRIGHT FLOOR POLISH** using a clean mop or polish applicator.

Drying time is normally around 30 minutes. Then a second coat is applied & allowed to dry. Coverage is dependant on the property of the floor covering. In general 5 litres of MERLIN F07 HI SOLIDS DRY BRIGHT FLOOR POLISH will cover approximately 250 square metres of floor.

SAFETY INFORMATION

Keep out of reach of children. Wear eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. Contains chloromethylisothiazolone, methylisothiazolone. May produce an allergic reaction.

For professional use only.













